



# SAFETY DATA SHEET

Date of issue/ Date of revision : 2012-03-17.

99745 Havwoods Accessories  
Ltd  
172 Brierley Road  
Walton Summit Centre  
Preston  
PR5 8AH  
UNITED KINGDOM

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : PARQUET BARRIER SEAL  
**Product code** : HL2005  
**Product type** : Oil Solventborne

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** Industrial PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) and Painting-related materials.

### 1.3 Details of the supplier of the safety data sheet

**Manufacturer** Sherwin-Williams Sweden Coatings KB  
Bellö, SE-570 32 Hjärtevad, SWEDEN  
Tel: +46 (0)381 261 00  
Fax: +46 (0)381 261 95  
info@beckeracroma.com

**e-mail address of person responsible for this SDS** : acroma.envir@sherwin.com

**Contact person** : Becker Acroma Ltd  
Weavers Business Centre  
6 Hamlet Road  
Haverhill  
Suffolk CB9 8EE  
UKsales@beckeracroma.com

### 1.4 Emergency telephone number

**Telephone number** : Sherwin-Williams Sweden, +46 (0)381 262 59, +46 (0)381 262 34, +46 (0)381 262 75

**Hours of operation** : Monday-Friday 08.00-16.30 CET

### National advisory body/Poison Center

**Telephone number** : National Poisons Information Service: 0870 600 6266/ +44 870 600 6266 OR 112

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Directive 1999/45/EC [DPD]

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

**Classification** : F; R11  
Xi; R36

**Physical/chemical hazards** : Highly flammable.

**Human health hazards** : Irritating to eyes.

See Section 16 for the full text of the R phrases or H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

## SECTION 2: Hazards identification

### 2.2 Label elements

Hazard symbol or symbols :



Indication of danger : Highly flammable, Irritant

Risk phrases : R11- Highly flammable.  
R36- Irritating to eyes.

Safety phrases : Not applicable.

Supplemental label elements : Not applicable.

### 2.3 Other hazards

Other hazards which do not result in classification : Not available

## SECTION 3: Composition/information on ingredients

Substance/mixture : Mixture

Product/ingredient name	Identifiers	%	Classification		Type
			67/548/EEC	Regulation (EC) No. 1272/2008 [CLP]	
Ethanol	EC: 200-578-6 CAS: 64-17-5 Index: 603-002-00-5	50-75	F; R11	Flam. Liq. 2, H225	[2]
Butanol	REACH #: 01-2119484630-38 EC: 200-751-6 CAS: 71-36-3 Index: 603-004-00-6	2,5-5	R10  Xn; R22 Xi; R41, R37/38 R67	Flam. Liq. 3, H226  Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 and H336	[1] [2]
Isopropyl alcohol	EC: 200-661-7 CAS: 67-63-0 Index: 603-117-00-0	2,5-5	F; R11 Xi; R36 R67	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	[1] [2]
Ethyl acetate	EC: 205-500-4 CAS: 141-78-6 Index: 607-022-00-5	1-2,5	F; R11 Xi; R36 R66, R67	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	[1] [2]
Methyl ethyl ketone	EC: 201-159-0 CAS: 78-93-3 Index: 606-002-00-3	1-2,5	F; R11 Xi; R36 R66, R67  See Section 16 for the full text of the R-phrases declared above.	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336  See Section 16 for the full text of the H statements declared above.	[1] [2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

**General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.

**Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 5 minutes, keeping eyelids open.

## SECTION 4: First aid measures

- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do not induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

### 4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See sections 3 and 15 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

See toxicological information (Section 11)

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Recommended: alcohol-resistant foam, CO<sub>2</sub>, powders, water spray.
- Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

### 5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.
- Special protective equipment for fire-fighters** : Appropriate breathing apparatus may be required.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : Exclude sources of ignition and ventilate the area. Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also Section 8 for additional information on hygiene measures.

- 6.2 Environmental precautions** : Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

- 6.3 Methods and materials for containment and cleaning up** : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Preferably clean with a detergent. Avoid using solvents.

- 6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

- 7.1 Precautions for safe handling** : Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap. Operators should wear antistatic footwear and clothing and floors should be of the conducting type. Keep away from heat, sparks and flame. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Avoid inhalation of dust from sanding. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Put on appropriate personal protective equipment (see Section 8). Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one. Comply with the health and safety at work laws.
- Information on fire and explosion protection**  
Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air.

- 7.2 Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations.
- Notes on joint storage**  
Keep away from: oxidizing agents, strong alkalis, strong acids.
- Additional information on storage conditions**  
Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorized access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

### 7.3 Specific end use(s)

- Recommendations** : Not available
- Industrial sector specific solutions** : Not available

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 8.1 Control parameters

#### Occupational exposure limits

Product/ingredient name	Exposure limit values
Ethanol	<b>EH40/2005 WELs (United Kingdom (UK), 8/2007).</b> TWA: 1000 ppm 8 hour(s). TWA: 1920 mg/m <sup>3</sup> 8 hour(s).
Butanol	<b>EH40/2005 WELs (United Kingdom (UK), 8/2007). Absorbed through skin.</b> STEL: 154 mg/m <sup>3</sup> 15 minute(s). STEL: 50 ppm 15 minute(s).
Isopropyl alcohol	<b>EH40/2005 WELs (United Kingdom (UK), 8/2007).</b> STEL: 1250 mg/m <sup>3</sup> 15 minute(s). STEL: 500 ppm 15 minute(s). TWA: 999 mg/m <sup>3</sup> 8 hour(s). TWA: 400 ppm 8 hour(s).
Ethyl acetate	<b>EH40/2005 WELs (United Kingdom (UK), 8/2007).</b> STEL: 400 ppm, 0 times per shift, 15 minute(s). TWA: 200 ppm, 0 times per shift, 8 hour(s).
Methyl ethyl ketone	<b>EH40/2005 WELs (United Kingdom (UK), 8/2007). Absorbed through skin.</b> STEL: 899 mg/m <sup>3</sup> 15 minute(s). STEL: 300 ppm 15 minute(s). TWA: 600 mg/m <sup>3</sup> 8 hour(s). TWA: 200 ppm 8 hour(s).

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances.

#### Derived effect levels

No DELs available.

#### Predicted effect concentrations

No PECs available.

### 8.2 Exposure controls

**Appropriate engineering controls** : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn.

#### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Use safety eyewear designed to protect against splash of liquids.

#### Skin protection

**Hand protection** : Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

**Gloves** : Gloves must be worn for all work that may result in soiling. Wear suitable gloves tested to EN374. Recommended: Silver Shield gloves. For specific applications, it is recommended to check the chemical resistance of the protective gloves mentioned above with the glove manufacturer. Do not wear the same gloves for other work. The recommendation for the type or types of glove to use when handling this product is based on information from the following source: European Solvents Industry Group (ESIG) & AnsellPro. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

## SECTION 8: Exposure controls/personal protection

- Body protection** : Personnel should wear antistatic clothing made of natural fibers or of high-temperature-resistant synthetic fibers.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.
- Recommended** : organic vapor (Type A, EN14387) and particulate filter , P3 (EN14387)
- Environmental exposure controls** : Do not allow to enter drains or watercourses.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Liquid.
- Odor** : Solvent.
- Odor threshold** : Not available (Not tested)
- pH** : Not applicable. (non-aqueous preparation)
- Melting point/freezing point** : Not available (Not tested)
- Initial boiling point and boiling range** : Not available (Not tested)
- Flash point** : Closed cup: 12°C [ASTM 6450]
- Evaporation rate** : Not available (Not tested)
- Flammability (solid, gas)** : Not available (Not tested)
- Burning time** : Not available (Not tested)
- Burning rate** : Not available (Not tested)
- Upper/lower flammability or explosive limits** : Lower : 1.4%-v/v, upper : 19%-v/v.
- Vapor pressure** : Not available (Not tested)
- Vapor density** : Vapors are heavier than air and may spread along floors.
- Relative density** : 0,88 g/cm<sup>3</sup>
- Solubility(ies)** : Not available (Not tested)
- Partition coefficient: n-octanol/water** : Not available (Not tested)
- Auto-ignition temperature** : Not available (Not tested)
- Decomposition temperature** : Not available (Not tested)
- Viscosity** : Not available
- Explosive properties** : Under normal conditions of storage and use, hazardous reactions will not occur.
- Oxidizing properties** : Under normal conditions of storage and use, hazardous reactions will not occur.
- VOC content**
- g/l** : 598
- %** : 68
- Dry content (%)** : 32

### 9.2 Other information

No additional information.

## SECTION 10: Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : Stable under recommended storage and handling conditions (see section 7).
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

## SECTION 10: Stability and reactivity

**10.4 Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products.

**10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

**10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

There are no data available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See sections 3 and 15 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Ethanol	LC50 Inhalation Vapor	Rat	124700 mg/m <sup>3</sup>	4 hours
Butanol	TDLo Oral	Mouse - Male	5 g/kg	-
	LC50 Inhalation Gas.	Rat	>8000 ppm	4 hours
	LC50 Inhalation Vapor	Rat	24000 mg/m <sup>3</sup>	4 hours
	LD50 Dermal	Rabbit	3400 mg/kg	-
Isopropyl alcohol	LD50 Oral	Rat	790 mg/kg	-
	LD50 Oral	Rat	5000 mg/kg	-
Ethyl acetate	LD50 Oral	Rat	5620 mg/kg	-
Methyl ethyl ketone	LD50 Dermal	Rabbit	6480 mg/kg	-

### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Ethanol	Eyes - Mild irritant	Rabbit	-	-	-
	Eyes - Moderate irritant	Rabbit	-	-	-
	Eyes - Severe irritant	Rabbit	-	-	-
	Skin - Mild irritant	Rabbit	-	-	-
	Skin - Moderate irritant	Rabbit	-	-	-
Butanol	Eyes - Severe irritant	Rabbit	-	-	-
	Skin - Moderate irritant	Rabbit	-	-	-
Isopropyl alcohol	Eyes - Moderate irritant	Rabbit	-	-	-
	Eyes - Severe irritant	Rabbit	-	-	-
Methyl ethyl ketone	Skin - Mild irritant	Rabbit	-	-	-
	Skin - Mild irritant	Rabbit	-	-	-
	Skin - Moderate irritant	Rabbit	-	-	-

**Other information** : Not available

## SECTION 12: Ecological information

### 12.1 Toxicity

There are no data available on the preparation itself.

Do not allow to enter drains or watercourses.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is not classified as dangerous for the environment.

## SECTION 12: Ecological information

Product/ingredient name	Result	Species	Exposure
Ethanol	Acute LC50 1000000 to 11500000 ug/L Marine water	Fish - Alburnus alburnus - 8 cm	96 hours
	Acute LC50 >100000 ug/L Fresh water	Fish - Pimephales promelas - Juvenile (Fledgling, Hatchling, Weanling) - 0,2 to 0,5 g	96 hours
Butanol	Acute EC50 1983000 ug/L Fresh water	Daphnia - Daphnia magna - 6 to 24 hours	48 hours
	Acute LC50 100 mg/L Fresh water	Fish - Lepomis macrochirus - 0,1 g	96 hours
Isopropyl alcohol	Acute LC50 1400000 to 1950000 ug/L Marine water	Crustaceans - Crangon crangon	48 hours
	Acute LC50 >1400000 ug/L	Fish - Gambusia affinis - 20 to 30 mm	96 hours
Ethyl acetate	Acute LC50 154000 ug/L Fresh water	Daphnia - Daphnia cucullata - 11 days	48 hours
	Acute LC50 212500 to 225420 ug/L Fresh water	Fish - Heteropneustes fossilis - 14,16 cm - 25,54 g	96 hours
Methyl ethyl ketone	Acute LC50 >520000 ug/L Fresh water	Daphnia - Daphnia magna - <=24 hours	48 hours
	Chronic NOEC <70000 ug/L Fresh water	Daphnia - Daphnia magna - <=24 hours	48 hours
	Chronic NOEC 400 ppm Marine water	Fish - Cyprinodon variegatus - Juvenile (Fledgling, Hatchling, Weanling) - 8 to 15 mm	96 hours

### 12.2 Persistence and degradability

**Conclusion/Summary** : Not available

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Butanol	-	-	Readily
Ethyl acetate	-	-	Readily

### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Butanol	0,88	2,7	low
Isopropyl alcohol	0,05	-	low
Ethyl acetate	0,73	30	low
Methyl ethyl ketone	1.8 to 2	-	low

### 12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available

**Mobility** : Not available

### 12.5 Results of PBT and vPvB assessment

**PBT** : Not applicable.

**vPvB** : Not applicable.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Do not allow to enter drains or watercourses.

Dispose of according to all federal, state and local applicable regulations.

### 13.1 Waste treatment methods

**Product**

## SECTION 13: Disposal considerations

**Methods of disposal** : The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

**European waste catalogue (EWC)** : 08 01 11\* waste paint and varnish containing organic solvents or other dangerous substances

**Hazardous waste** : Yes.

### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Ensure packaging is completely empty before recycling. Dispose of uncured residues in the same way as the product itself.

Type of packaging	European waste catalogue (EWC)
Plastic.	EWC 15 01 02 plastic packaging
Metal.	EWC 15 01 04 metallic packaging

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

**Contaminated packaging** : EWC 15 01 10\* packaging containing residues of or contaminated by dangerous substances

## SECTION 14: Transport information

	ADR/RID	IMDG	IATA
<b>14.1 UN number</b>	1263	1263	1263
<b>14.2 UN proper shipping name</b>	Paint related material	Paint related material	Paint related material
<b>14.3 Transport hazard class(es)</b>	3 	3 	3 
<b>14.4 Packing group</b>	II	II	II
<b>14.5 Environmental hazards</b>	No.	No.	No.
<b>14.6 Special precautions for user</b>	<b>Transport within user's premises:</b> always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.	<b>Transport within user's premises:</b> always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.	<b>Transport within user's premises:</b> always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
<b>Additional information</b>	<b>Special provisions</b> 640 (C) <b>Tunnel code</b> (D/E)	<b>Emergency schedules (EmS)</b> F-E,S-E	-

## SECTION 14: Transport information

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not applicable.

## SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

### EU Regulation (EC) No. 1907/2006 (REACH)

#### Annex XIV - List of substances subject to authorization

##### Substances of very high concern

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

#### Other EU regulations

**Europe inventory** : All components are listed or exempted.

**Integrated pollution prevention and control list (IPPC) - Air** : Not listed

**Integrated pollution prevention and control list (IPPC) - Water** : Not listed

**Industrial use** : The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

#### International regulations

**Chemical Weapons Convention List Schedule I Chemicals** : Not listed

**Chemical Weapons Convention List Schedule II Chemicals** : Not listed

**Chemical Weapons Convention List Schedule III Chemicals** : Not listed

**15.2 Chemical Safety Assessment** : This product contains substances for which Chemical Safety Assessments are still required.

## SECTION 16: Other information

**CEPE code** : 1

Indicates information that has changed from previously issued version.

**Abbreviations and acronyms** : ATE = Acute Toxicity Estimate  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
DNEL = Derived No Effect Level  
EUH statement = CLP-specific Hazard statement  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number

## SECTION 16: Other information

<b>Full text of abbreviated H statements</b>	: H224 Extremely flammable liquid and vapor. H225 Highly flammable liquid and vapor. H226 Flammable liquid and vapor. H302 Harmful if swallowed. H315 Causes skin irritation. H318 Causes serious eye damage. H319 Causes serious eye irritation. H335 May cause respiratory irritation. May cause drowsiness and dizziness. and H336 H336 May cause drowsiness and dizziness.
<b>Full text of classifications [CLP/GHS]</b>	: Acute Tox. 4, H302 ACUTE TOXICITY: ORAL - Category 4 Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 Flam. Liq. 1, H224 FLAMMABLE LIQUIDS - Category 1 Flam. Liq. 2, H225 FLAMMABLE LIQUIDS - Category 2 Flam. Liq. 3, H226 FLAMMABLE LIQUIDS - Category 3 Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2 STOT SE 3, H335 and H336 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Respiratory tract irritation and Narcotic effects] - Category 3  STOT SE 3, H336 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Narcotic effects] - Category 3
<b>Full text of abbreviated R phrases</b>	: R11- Highly flammable. R10- Flammable. R22- Harmful if swallowed. R41- Risk of serious damage to eyes. R36- Irritating to eyes. R37/38- Irritating to respiratory system and skin. R66- Repeated exposure may cause skin dryness or cracking. R67- Vapors may cause drowsiness and dizziness.
<b>Full text of classifications [DSD/DPD]</b>	: F - Highly flammable Xn - Harmful Xi - Irritant
<b>Date of printing</b>	: 2012-07-27.
<b>Date of issue/ Date of revision</b>	: 2012-03-17.
<b>Date of previous issue</b>	: 2011-11-13.
<b>Version</b>	: 2
<b><u>Notice to reader</u></b>	

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.